# BRASS STANDARD DRY GAUGE

DATE
: 11/23/2026 09:51 PM

SKU
: 14565

BRAND
: DIXON VALVE

MODEL
: GBR15




** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

Applications:
All of the gauges supplied by Dixon are designed for long, reliable service under rugged conditions. Typical applications include those on pumps, hydraulic and pneumatic systems, compressors, machine tools and many other installations where it is necessary to have a gauge with a non-corrosive movement.

Specifications:
ASME B40.100 Grade B (± 3/2/3% accuracy)

Construction:
Copper alloy bourdon tube
Dual PSI / kPa scale dial
Polished brass case
Polished brass ring

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

## TECHNICAL SPECIFICATIONS

| | |
|---|---|
| **Factory Part Number** | GBR15 |
| **Figure Interval** | 3 |
| **Material** | Brass |
| **Minor Gradient** | .2 |
| **Mount** | 1/4" lower mount |
| **Pressure Range** | 0-15 PSI |
| **Size** | 2-1/2" Face |



2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

## TECHNICAL SPECIFICATIONS

| | |
|---|---|
| **Temperature Range** | -40°F to 140°F (-40°C to 60°C) |
| **Weight Lb** | 0.3600 |



KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us