BRASS STANDARD DRY GAUGE

DATE
: 11/23/2026 09:49 PM

SKU
: 14568

BRAND
: DIXON VALVE

MODEL
: GBR200



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

Applications:
All of the gauges supplied by Dixon are designed for long, reliable service under rugged conditions. Typical applications include those on pumps, hydraulic and pneumatic systems, compressors, machine tools and many other installations where it is necessary to have a gauge with a non-corrosive movement.

Specifications:
ASME B40.100 Grade B (± 3/2/3% accuracy)

Construction:
Copper alloy bourdon tube
Dual PSI / kPa scale dial
Polished brass case
Polished brass ring

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	GBR200
Figure Interval	50
Material	Brass
Minor Gradient	5
Mount	1/4" lower mount
Pressure Range	0-200 PSI
Size	2-1/2" Face

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Temperature Range	-40°F to 140°F (-40°C to 60°C)
Weight Lb	0.3600

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us