WELDING GAUGE



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 07:21 PM

SKU
: 14583

BRAND
: DIXON VALVE

MODEL
: GBRW60

Applications:
All of the gauges supplied by Dixon are designed for long, reliable service under rugged conditions. Typical applications include those on pumps, hydraulic and pneumatic systems, compressors, machine tools and many other installations where it is necessary to have a gauge with a non-corrosive movement.

Specifications:
± 3-2-3% accuracy according to ASME B40.100 Grade B

Construction:
Copper alloy bourdon tube
"USE NO OIL" written in red on face
Stainless steel case
Twist-lock polycarbonate window
Copper alloy bourdon tube

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Factory Part Number	GBRW60
Figure Interval	10
Material	Brass
Minor Gradient	1
Mount	1/4" lower mount
Pressure Range	0-60 PSI
Size	2-1/2" Face
Temperature Range	-40°F to 140°F (-40°C to 60°C)
Weight Lb	0.4380

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us