ABS STANDARD DRY GAUGE LOWER MOUNT



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 08:14 PM

SKU
: 14683

BRAND
: DIXON VALVE

MODEL
: GL120

Applications:
All of the gauges supplied by Dixon are designed for long, reliable service under rugged conditions. Typical applications include those on pumps, hydraulic and pneumatic systems, compressors, machine tools and many other installations where it is necessary to have a gauge with a non-corrosive movement.

Specifications:
ASME B40.1, Grade B (± 3-2-3% accuracy)

Features:
PowerFlex™ movement with polyester segment, designed to resist the effects of shock, vibration and pulsation.

Construction:
Polycarbonate window
Black aluminum pointer
ABS plastic case, corrosion resistant
C-shaped bronze safety bourdon tube
Lower mount

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Factory Part Number	GL120
Figure Interval	5
Minor Gradient	1
Mount	1/4"
Pressure Range	0-60 PSI
Size	2" Face
Temperature Range	-40°F to 150°F (-40°C to 65.6°C)
Weight Lb	0.1700

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us