ABS STANDARD DRY GAUGE LOWER MOUNT



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 09:49 PM

SKU
: 14707

BRAND
: DIXON VALVE

MODEL
: GL350

Applications:
All of the gauges supplied by Dixon are designed for long, reliable service under rugged conditions. Typical applications include those on pumps, hydraulic and pneumatic systems, compressors, machine tools and many other installations where it is necessary to have a gauge with a non-corrosive movement.

Specifications:
ASME B40.1, Grade B (± 3-2-3% accuracy)

Features:
PowerFlex™ movement with polyester segment, designed to resist the effects of shock, vibration and pulsation.

Construction:
Polycarbonate window
Black aluminum pointer
ABS plastic case, corrosion resistant
C-shaped bronze safety bourdon tube
Lower mount

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Factory Part Number	GL350
Figure Interval	50
Minor Gradient	10
Mount	1/4"
Pressure Range	0-600 PSI
Size	2-1/2" Face
Temperature Range	-40°F to 150°F (-40°C to 65.6°C)
Weight Lb	0.2400

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us