BRASS LIQUID FILLED GAUGE LOWER MOUNT



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 09:02 PM

SKU
: 14736

BRAND
: DIXON VALVE

MODEL
: GLBR300

Applications:
All of the gauges supplied by Dixon are designed for long, reliable service under rugged conditions. Typical applications include those on pumps, hydraulic and pneumatic systems, compressors, machine tools and many other installations where it is necessary to have a gauge with a non-corrosive movement.

Specifications:
± 2-1-2% accuracy

Construction:
Glycerin filled
Solid cast brass case with ABS cover ring
Acrylic window with membrane assembly
Copper alloy bourdon tube
Brass movement with highly polished bearing surfaces

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Factory Part Number	GLBR300
Figure Interval	50
Material	Brass
Minor Gradient	5
Mount	1/4"
Pressure Range	0-300 PSI
Size	2-1/2" Face
Temperature Range	-4°F to 140°F (-20°C to 60°C)
Weight Lb	0.8200

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us