LIQUID FILLED STAINLESS CASE GAUGE LOWER MOUNT



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 08:53 PM

SKU
: 14782

BRAND
: DIXON VALVE

MODEL
: GLS425

Applications:
All of the gauges supplied by Dixon are designed for long, reliable service under rugged conditions. Typical applications include those on pumps, hydraulic and pneumatic systems, compressors, machine tools and many other installations where it is necessary to have a gauge with a non-corrosive movement.

Specifications:
ASME B40.100, Grade A (± 2-1-2% accuracy)

Features:
PowerFlex™ movement with polyester segment, designed to resist the effects of shock, vibration and pulsation.

Construction:
Copper alloy Bourdon Tube
White Aluminum Dial with Black Numerals and Black Aluminum Pointer
1/4" NPT brass connection
Glycerin filled
Polycarbonate window

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Factory Part Number	GLS425
Figure Interval	50
Minor Gradient	5
Mount	1/4" Lower Mount
Pressure Range	0-300 PSI
Size	2-1/2" Face
Temperature Range	-4°F to 150°F (-20°C to 65°C)
Weight Lb	0.5100

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us