LIQUID FILLED STAINLESS CASE GAUGE LOWER MOUNT



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 09:17 PM

SKU
: 14784

BRAND
: DIXON VALVE

MODEL
: GLS430

Applications:
All of the gauges supplied by Dixon are designed for long, reliable service under rugged conditions. Typical applications include those on pumps, hydraulic and pneumatic systems, compressors, machine tools and many other installations where it is necessary to have a gauge with a non-corrosive movement.

Specifications:
ASME B40.100, Grade A (± 2-1-2% accuracy)

Features:
PowerFlex™ movement with polyester segment, designed to resist the effects of shock, vibration and pulsation.

Construction:
Copper alloy Bourdon Tube
White Aluminum Dial with Black Numerals and Black Aluminum Pointer
1/4" NPT brass connection
Glycerin filled
Polycarbonate window

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Factory Part Number	GLS430
Figure Interval	100
Minor Gradient	10
Mount	1/4" Lower Mount
Pressure Range	0-600 PSI
Size	2-1/2" Face
Temperature Range	-4°F to 150°F (-20°C to 65°C)
Weight Lb	0.5100

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us