LIQUID FILLED STAINLESS CASE GAUGE CENTER BACK MOUNT



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 10:49 PM

SKU
: 14792

BRAND
: DIXON VALVE

MODEL
: GLSC410

Applications:
All of the gauges supplied by Dixon are designed for long, reliable service under rugged conditions. Typical applications include those on pumps, hydraulic and pneumatic systems, compressors, machine tools and many other installations where it is necessary to have a gauge with a non-corrosive movement.

Specifications:
ASME B40.100, Grade A (± 2-1-2% accuracy)

Features:
PowerFlex™ movement with polyester segment, designed to resist the effects of shock, vibration and pulsation.

Construction:
Copper alloy Bourdon Tube
White Aluminum Dial with Black Numerals and Black Aluminum Pointer
1/4" NPT brass connection
Glycerin filled
Polycarbonate window

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Factory Part Number	GLSC410
Figure Interval	10
Minor Gradient	1
Mount	1/4" Center Back Mount
Pressure Range	0-60 PSI
Size	2-1/2" Face
Temperature Range	-4°F to 150°F (-20°C to 65°C)
Weight Lb	0.5500

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us