# LIQUID FILLED STAINLESS CASE GAUGE CENTER BACK MOUNT




** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 09:54 PM

SKU
: 14799

BRAND
: DIXON VALVE

MODEL
: GLSC435

Applications:
All of the gauges supplied by Dixon are designed for long, reliable service under rugged conditions. Typical applications include those on pumps, hydraulic and pneumatic systems, compressors, machine tools and many other installations where it is necessary to have a gauge with a non-corrosive movement.

Specifications:
ASME B40.100, Grade A (± 2-1-2% accuracy)
Figure interval: 200
Minor gradient: 20

Features:
PowerFlex™ movement with polyester segment, designed to resist the effects of shock, vibration and pulsation.

Construction:
Copper alloy Bourdon Tube
White Aluminum Dial with Black Numerals and Black Aluminum Pointer
1/4" NPT brass connection
Glycerin filled
Polycarbonate window

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov



2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

## TECHNICAL SPECIFICATIONS

| | |
|---|---|
| **Factory Part Number** | GLSC435 |
| **Figure Interval** | 200 |
| **Minor Gradient** | 10 |
| **Mount** | 1/4" Center Back Mount |
| **Pressure Range** | 0-1000 PSI |
| **Size** | 2-1/2" Face |
| **Temperature Range** | -4°F to 150°F (-20°C to 65°C) |
| **Weight Lb** | 0.5400 |



KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us