STAINLESS LIQUID FILLED GAUGE LOWER MOUNT



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 08:47 PM

SKU
: 14807

BRAND
: DIXON VALVE

MODEL
: GLSS15

Applications:
Stainless steel gauges provide the corrosion resistance and durability of a permanently sealed gauge. Designed for severe service applications.

Specifications:
± 2-1-2% accuracy

Construction:
Polycarbonate window
1/4" NPT lower mount stainless connector
304 stainless case and crimp ring
Glycerin filled

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	GLSS15
Figure Interval	3
Material	Stainless Steel
Minor Gradient	.2
Mount	1/4" Lower Mount
Pressure Range	0-15 PSI
Size	2-1/2" Face
Temperature Range	-4°F to 140°F (-20°C to 60°C)

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Weight Lb	0.5700

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us