# DQC H-SERIES ISO-B HIGH VOLUME FEMALE PLUG





** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 11:44 PM

SKU
: 24464

BRAND
: DIXON VALVE

MODEL
: H12F12-S

Features:
Poppet style shut-off valves
Designed to prevent fluid loss when disconnected

Construction:
Machined components are manufactured using solid bar stock
Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.

Available Options:
Contact Dixon for all available option adders

Compatibility & Interchange Data:
Meets dimensional requirements of ISO 7241 Series B
Interchangeable with Parker-Hannifin 60 Series, Snap-Tite 72-Series, Hansen HK-Series, Faster Series 'HNV', Aeroquip/Eaton FD45, Stucchi Series IRB/IRBO/IRBX

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov



2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

## TECHNICAL SPECIFICATIONS

| | |
|---|---|
| **Body Size** | 1-1/2" |
| **Burst Pressure** | 8500 PSI (600 bar) |
| **Factory Part Number** | H12F12-S |
| **Hex** | 2-5/8" |
| **Length** | 4.76" (120.9mm) |
| **Material** | 303 Stainless Steel |
| **Maximum OD** | 2.88" (73.2mm) |
| **Maximum Operating Pressure** | 1500 PSI (100 bar) |
| **Temperature Range** | -40°F to +250°F (-40°C to +121°C) |
| **Thread** | Female NPTF |
| **Thread Size** | 1-1/2" - 11-1/2 |
| **Weight Lb** | 3.0600 |



KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us