# DQC H-SERIES ISO-B MALE PLUG





** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 11:41 PM

SKU
: 24524

BRAND
: DIXON VALVE

MODEL
: H4M6-S

Features:
Poppet style shut-off valves
Designed to prevent fluid loss when disconnected

Construction:
Machined components are manufactured using solid bar stock
Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.
Steel componentry is plated using ROHS Compliant Trivalent Chrome.
Steel Nipples are hardened to provide heavy duty performance and resist brinelling.

Available Options:
Contact Dixon for all available option adders

Compatibility & Interchange Data:
Meets dimensional requirements of ISO 7241 Series B
Interchangeable with Parker-Hannifin 60 Series, Snap-Tite 72-Series, Hansen HK-Series, Faster Series 'HNV', Aeroquip/Eaton FD45, Stucchi Series IRB/IRBO/IRBX

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov



2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

## TECHNICAL SPECIFICATIONS

| | |
|---|---|
| **Body Size** | 1/2" |
| **Burst Pressure** | 27500 PSI (1900 bar) |
| **Factory Part Number** | H4M6-S |
| **Hex** | 1-1/16" |
| **Length** | 2.13" (58.7mm) |
| **Material** | 303 Stainless Steel |
| **Maximum OD** | 1.17" (29.7mm) |
| **Maximum Operating Pressure** | 3500 PSI (240 bar) |
| **Temperature Range** | -40°F to +250°F (-40°C to +121°C) |
| **Thread** | Male NPTF |
| **Thread Size** | 3/4"-14 |



KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us