500# NITRILE COVERED FIRE HOSE LIGHT DUTY



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 08:54 PM

SKU
: 24556

BRAND
: DIXON VALVE

MODEL
: H525R50RBF

Applications:
Ideal for industrial and construction washdown and discharge applications.
Light Duty

Construction:
Outer: Red, Thin ribbed nitrile
Tube: Nitrile

Available Options:
Consult Dixon for pricing and availability of 25' lengths, other colors, threads and configurations.

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Bowl Size	2-13/16"
Color	Red
Coupling Type	Brass Expansion ring
Factory Part Number	H525R50RBF
Hose Size	2-1/2"
Proof Pressure	500 PSI
Service Test Pressure	250 PSI
Style	Rocker Lug
Thread	NST (NH)
Weight Lb	28.8800

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Working Pressure	225 PSI

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us