# 500# NITRILE COVERED FIRE HOSE LIGHT DUTY




** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 09:00 PM

SKU
: 24557

BRAND
: DIXON VALVE

MODEL
: H525R50UC

Applications:
Ideal for industrial and construction washdown and discharge applications.
Light Duty

Construction:
Outer: Red, Thin ribbed nitrile
Tube: Nitrile

Available Options:
Consult Dixon for pricing and availability of 25' lengths, other colors, threads and configurations.

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

## TECHNICAL SPECIFICATIONS

| | |
|---|---|
| **Bowl Size** | 2-13/16" |
| **Color** | Red |
| **Coupling Type** | Uncoupled |
| **Factory Part Number** | H525R50UC |
| **Hose Size** | 2-1/2" |
| **Proof Pressure** | 500 PSI |
| **Service Test Pressure** | 250 PSI |
| **Weight Lb** | 23.0000 |
| **Working Pressure** | 225 PSI |



2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us