NITRILE COVERED FIRE HOSE HEAVY DUTY



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 09:31 PM

SKU
: 14974

BRAND
: DIXON VALVE

MODEL
: H615Y50RAF

Applications:
Ideal for heavy-duty washdown, refineries and power plants

Construction:
Outer: Yellow, Thick Ribbed Nitrile
Tube: Nitrile

Safety notes:
Under no circumstance should the hose be used beyond the working pressure of the fittings to which it is coupled.
Assembled hose should be hydrostatically proof tested before use, and thereafter in accordance with NFPA 1962.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Bowl Size	1-13/16"
Color	Yellow
Coupling Type	Aluminum Expansion Ring, Rocker Lug
Factory Part Number	H615Y50RAF
Hose Size	1-1/2"
Proof Pressure	600 PSI
Service Test Pressure	300 PSI
Thread	NST (NH)
Weight Lb	15.2000
Working Pressure	270 PSI

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us