H8 SERIES FORGED BELLOWS SEAL GATE VALVE



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 11:55 PM

SKU
: 27536

BRAND
: DIXON VALVE

MODEL
: H8CF1200G

Applications:
For use in applications where leakage into or out of the valve is unacceptable such as heat transfer oil, toxic fluids, steam and regulated media.
Our bellows technology keeps corrosive or harmful atmospheric conditions from entering the process.
Specifications:
ANSI/API Class 150-800 available
Valve tested to ASME B16.34 / API 598
Meets MSS SP-117
5-year bellow warranty
Assembled and tested in a US ISO 9001:2015 certified facility
Features:
Stainless steel bellows (Inconel™ bellows available) provides longer life and maximum corrosion resistance
Zero stem leakage eliminates media loss and satisfies environmental regulations
Zero maintenance results in lower operating costs / no downtime
Reduce monitoring costs
Construction:
Three stem seals for safety: metallic bellows, graphite packing, backseat in open position
Hardfaced Stellite® 6 seating surface provides long life
Welded bonnet
Class 150 RF schedule 40
Available Options:
Additional alloys, trims, end configurations and sizes are available, contact Dixon for details.
Inconel® 625 bellows
Note:
Stellite™ is a registered trademark of Thermadyne.
Inconel™ is a trademark of Huntington Alloys, inc.

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

Dixon recommends that all valve assemblies be tested in accordance with ASME and API recommendations and be inspected regularly to ensure that their use remains appropriate and that they are not damaged.

At no charge, Dixon is available to consult, train and recommend the proper selection and application of all valves we sell. We strongly recommend that distributers and end users make use of Dixon\'s Testing and Recommendation Services. Call 800.355.1991 to learn more.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Pressure Class	CL 800
Material	A105 carbon steel
Factory Part Number	H8CF1200G
Size	2"
Type	Gate, forged, welded bonnet
Weight Lb	39.0000

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us