
# DQC HS-SERIES ISO-B STEAM INTERCHANGE FEMALE PLUG



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 10:27 PM

SKU
: 24637

BRAND
: DIXON VALVE

MODEL
: HS3BF3-B

Applications:
Designed exclusively for steam applications

Construction:
Machined components are manufactured using solid bar stock
Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.
Special high-temp EPDM O-rings designed for steam service

Compatibility & Interchange Data:
Interchangeable to ISO7241 Series 'B'
Parker 60-Series Steam Couplings

Safety notes:
Maximum working pressure has been calculated using standard saturated steam at 194°C (382°F) for general purpose continuous service. For advanced operating pressure or super-heated steam applications, contact Dixon for further information.
Warning: Do not disconnect under pressure!
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov



2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

## TECHNICAL SPECIFICATIONS

| | |
|---|---|
| **Body Size** | 3/8" |
| **Factory Part Number** | HS3BF3-B |
| **Hex** | 7/8" |
| **Length** | 1.70" (43.2 mm) |
| **Material** | Brass |
| **Maximum OD** | 0.97" (24.6 mm) |
| **Pressure Rating** | Rated to 200 PSI gauge saturated steam 382°F (194°C) |
| **Temperature Range** | -70°F to +400°F (-57°C to +204°C) |
| **Thread** | Female BSPP |
| **Thread Size** | 3/8"-19 |



KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us