HSC SERIES SPRING CHECK VALVE

DATE
: 11/23/2026 06:56 PM

SKU
: 15397

BRAND
: DIXON VALVE

MODEL
: HSCE075



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

Applications:
Spring check valves are designed to prevent reverse flow. The concentric design makes them ideal for vertical applications.

Features:
Machined from solid bar
Standard O-ring and gasket seal design
Can be serviced in field (no special tools required)
Finish: sanitary polish 32 Ra

Available Options:
Various end connections available

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Cracking Presure	4.0 PSI
Elastomer	EPDM
Material	316L Stainless Steel
Maximum Operating Pressure	145 PSI
Optional Pkg/Box Qty	1
Factory Part Number	HSCE075
Size	3/4"
Style	Clamp Connection
Temperature Range	15°F to 200°F (-9.4°C to 93°C)

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Weight Lb	1.1000

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us