HSC SERIES SPRING CHECK VALVE



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 06:56 PM

SKU
: 15407

BRAND
: DIXON VALVE

MODEL
: HSCE300

Applications:
Spring check valves are designed to prevent reverse flow. The concentric design makes them ideal for vertical applications.

Features:
Single piece upper body spider design
Machined from solid bar
Standard O-ring and gasket seal design
Can be serviced in field (no special tools required)
Finish: sanitary polish 32 Ra

Available Options:
Various end connections available

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Cracking Presure	0.5 PSI
Elastomer	EPDM
Material	316L Stainless Steel, CF8M (plunger)
Maximum Operating Pressure	145 PSI
Factory Part Number	HSCE300
Size	3"
Style	Clamp Connection
Temperature Range	15°F to 200°F (-9.4°C to 93°C)

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Weight Lb	4.2500

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us