HSC SERIES SPRING CHECK VALVE

DATE
: 11/23/2026 07:41 PM

SKU
: 15423

BRAND
: DIXON VALVE

MODEL
: HSCV300



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

Applications:
Spring check valves are designed to prevent reverse flow. The concentric design makes them ideal for vertical applications.

Features:
Single piece upper body spider design
Machined from solid bar
Standard O-ring and gasket seal design
Can be serviced in field (no special tools required)
Finish: sanitary polish 32 Ra

Available Options:
Various end connections available

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Cracking Presure	0.5 PSI
Elastomer	FKM
Material	316L Stainless Steel, CF8M (plunger)
Maximum Operating Pressure	145 PSI
Factory Part Number	HSCV300
Size	3"
Style	Clamp Connection
Temperature Range	15°F to 200°F (-9.4°C to 93°C)

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Weight Lb	4.2500

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us