
DQC HT-SERIES FLUSHFACE FEMALE THREADED PLUG







** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 06:45 PM

SKU
: 15541

BRAND
: DIXON VALVE

MODEL
: HT12F12

Specifications:
Rated pressure for connected Steel Coupler and Steel Plug: 3,000 PSI (207 bar) Maximum Working and 12,000 PSI (828 bar) burst
Rated pressure for uncoupled Steel Plug: 3,000 PSI (207 bar) Maximum Working and 12,000 PSI (828 bar) burst

Features:
High flow performance, compact profile
Easily rebuildable!
High strength laser-cut valve guide maximizes valve stability while minimizing flow restriction.
Improved sealing system incorporates a high performance molded polyurethane or O-ring energized PTFE valve seal.

Construction:
Machined components are manufactured using solid bar stock
Steel nipples are hardened to provide resistance to brinelling during impulse service.
Has Nitrile-Energized PTFE valve seals, with a temperature range of-40° to +250°F
Ancillary nipple seals are Nitrile (Buna-N), with a temperature range of-40°F to +250°F
PTFE or TPC-ET Anti-Extrusion ring protects main coupling valve seal from dynamic impulse pressure damage.

Available Options:
Contact Dixon for all available option adders
Oxy-clean treatment is available

Compatibility & Interchange Data:
Interchangeable to ISO16028

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

Conforms to ISO16028 interchange standard interchangeable with Eaton/Hansen FF, Parker FEM, Snap-tite 74, Faster FFH/2FFN/2FFI, Stucchi A/FIRG and Holmbury HQ/A/FIMC

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	1-1/2"
Factory Part Number	HT12F12
Hex	2-1/2"
Length	4.25"
Material	Steel
Maximum OD	2.75"
Pressure Rating	See Product Details
Thread	Female NPTF
Thread Size	1-1/2"-11-1/2
Weight Lb	3.4300

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us