
DQC HT-SERIES FLUSHFACE FEMALE THREADED PLUG







** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 07:06 PM

SKU
: 15643

BRAND
: DIXON VALVE

MODEL
: HT8BF8-SS

Specifications:
Rated pressure for connected 316 Stainless Steel Coupler and 316 Stainless Steel Plug: 2,920 PSI (201 bar) Maximum Working and 14,600 PSI (1,007 bar) burst

Features:
High flow performance, compact profile
Easily rebuildable!
High strength laser-cut valve guide maximizes valve stability while minimizing flow restriction.
Improved sealing system incorporates a high performance molded polyurethane or O-ring energized PTFE valve seal.

Construction:
Machined components are manufactured using solid bar stock
Has Nitrile-Energized PTFE valve seals, with a temperature range of-40° to +250°F
Ancillary nipple seals are Nitrile (Buna-N), with a temperature range of-40°F to +250°F
PTFE or TPC-ET Anti-Extrusion ring protects main coupling valve seal from dynamic impulse pressure damage.

Available Options:
Contact Dixon for all available option adders
Oxy-clean treatment is available

Compatibility & Interchange Data:
Interchangeable to ISO16028
Conforms to ISO16028 interchange standard interchangeable with Eaton/Hansen FF, Parker FEM, Snap-tite 74, Faster FFH/2FFN/2FFI, Stucchi A/FIRG and Holmbury HQ/A/FIMC

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	1"
Factory Part Number	HT8BF8-SS
Hex	1-3/4"
Length	3.50" (88.9mm)
Material	316 Stainless Steel
Maximum OD	1.92" (48.8mm)
Pressure Rating	See Product Details
Thread	Female BSPP
Thread Size	1"-11
Weight Lb	1.6900

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us