HAMMER UNION 1002 SERIES

DATE
: 11/23/2026 10:42 PM

SKU
: 15733

BRAND
: DIXON VALVE

MODEL
: HU1002300BW





** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

Use:
For use in high pressure systems and truck mounting applications running water, oil or mud up to 10,000 PSI NSCWP (non-shock cold working pressure)

Features:
Lip type seal ring minimizes fluid flow turbulence while creating a pressure seal

Construction:
Blue sub, red nut

Safety notes:
Hammer unions work at extremely high pressures. Mismatching components of one series with another (i.e. series 602 with series 1502) can lead to destruction of property, serious bodily injury or death.
Pressure rating given at ambient temperature 70°F/21°C.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	HU1002300BW
Material	Forged Steel, Schedule XXS
Maximum Operating Pressure	10000 PSI NSCWP
Size	3"
Style	Buttweld
Temperature Range	-20°F to 250°F (-29°C to 121°C)
Weight Lb	25.0000

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us