HAMMER UNION 1502 SERIES

DATE
: 11/24/2026 01:13 AM

SKU
: 15748

BRAND
: DIXON VALVE

MODEL
: HU1502200



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

Use:
For use in extreme high pressure applications running water, oil or mud up to 15,000 PSI NSCWP (non-shock cold working pressure)

Features:
Lip type seal ring minimizes fluid flow turbulence while creating a pressure seal

Construction:
Red sub, blue nut

Safety notes:
Hammer unions work at extremely high pressures. Mismatching components of one series with another (i.e. series 602 with series 1502) can lead to destruction of property, serious bodily injury or death.
Pressure rating given at ambient temperature 70°F/21°C.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	HU1502200
Material	Forged Steel
Maximum Operating Pressure	15000 PSI NSCWP
Size	2"
Style	Threaded
Temperature Range	-20°F to 250°F (-29°C to 121°C)
Weight Lb	20.2500

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us