HAMMER UNION 206 SERIES





** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 10:58 PM

SKU
: 15771

BRAND
: DIXON VALVE

MODEL
: HU206300

Use:
Used in general service applications running air, water, oil or gas up to 2,000 PSI NSCWP (non-shock cold working pressure)

Features:
Nitrile O-ring mounted sub provides excellent sealing properties

Construction:
Grey sub, blue nut

Safety notes:
Hammer unions work at extremely high pressures. Mismatching components of one series with another (i.e. series 602 with series 1502) can lead to destruction of property, serious bodily injury or death.
Pressure rating given at ambient temperature 70°F/21°C.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	HU206300
Material	Forged Steel
Maximum Operating Pressure	2000 PSI NSCWP
Size	3"
Style	Threaded
Temperature Range	-20°F to 250°F (-29°C to 121°C)
Weight Lb	15.0000

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us