LOW PROFILE HAMMER UNION CAP



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 08:59 PM

SKU
: 15791

BRAND
: DIXON VALVE

MODEL
: HUC206600

Applications:
Prevents leakage of hydraulic fracturing fluids from hammer union connections used on manifolds and hose assemblies.
Hammer union caps and plugs can be used in pressurized service or as dust caps/plugs on site or when transferring equipment.

Specifications:
Forged steel meets AISI standards

Features:
Forged steel construction ensures longevity, reliability and performance
Low profile design for tight applications
Designed with reusable bull plug to rebuild cap

Construction:
Iron bull plug to ASTM standards
O-ring is Buna-N (O440BU)
Figure 100/200 has a metal-to-metal sealing surface and Figure 206 is similar to Figure 200 with a secondary seal to supplement the metal-to-metal design.

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov
Working pressure for Figure 100 = 1000 PSI and Figure 200/206 = 2000 PSI.

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Description	Blanking cap, includes nut/plug body, o-ring and retaining ring
Factory Part Number	HUC206600
Mandatory Pkg/Box Qty	1
Material	Forged steel nut, Iron bull plug
Size	6"
Style	Figure 100/200/206
Weight Lb	32.5000
Working Pressure	See Safety Notes

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us