DIXON® FEMALE FRAC FITTING

DATE
: 11/23/2026 10:19 PM



SKU
: 15795

BRAND
: DIXON VALVE

MODEL
: HUF100300CS

** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

Applications:
Used in the fast paced transfer of water and sand slurry at hydraulic fracturing sites.

Use:
Designed to work with Dixon King Crimp Ferrules.

Features:
One-piece design eliminates leak path experienced with two-piece threaded systems
Durable and safe with reliable hose retention when crimped as specified

Construction:
Machined Iron to ASTM standards
All stems are zinc plated

Compatibility & Interchange Data:
Interchangeable with current fittings; phase them into your current operation

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov
400 PSI working pressure with a minimum 4:1 safety factor (hose burst: hose working pressure) is only achieved with: 3" sizes using standard crimp ferrules

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Factory Part Number	HUF100300CS
Material	Iron
Size	3"
Style	Figure 100
Weight Lb	6.0000
Working Pressure	400 PSI at 70°F (21°C)

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us