DIXON® FEMALE FRAC FITTING

DATE
: 11/24/2026 10:16 PM

SKU
: 15800

BRAND
: DIXON VALVE

MODEL
: HUF206400CS



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

Applications:
Used in the fast paced transfer of water and sand slurry at hydraulic fracturing sites.

Use:
Designed to work with Dixon King Crimp Ferrules.

Specifications:
Machined malleable iron stems to ASTM A47 standard

Features:
One-piece design eliminates leak path experienced with two-piece threaded systems
Long lasting and dependable hammer nut is forged to ASTM 105N standards

Construction:
Machined iron to ASTM standards; all stems are zinc plated

Compatibility & Interchange Data:
Interchangeable with current fittings; phase them into your current operation

Note:
Water and petroleum transfer hoses rated from 100 to 300 PSI WP (4:1 SF) have excellent test results with the standard King Crimp ferrules CF400-xxCS)

Safety notes:
400 PSI working pressure with a minimum 4:1 safety factor (hose burst: hose working pressure) is only achieved with: 4" size requires heavy duty (HD) crimp ferrules, CF400-6CSHD through CF400-16CSHD and heavy duty stems
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Factory Part Number	HUF206400CS
Material	Iron
Size	4"
Style	Figure 200/206
Weight Lb	8.7500
Working Pressure	400 PSI at 70°F (21°C)

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us