DIXON® MALE FRAC FITTING WITH NUT



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 10:14 PM

SKU
: 15813

BRAND
: DIXON VALVE

MODEL
: HUM206300CS

Applications:
Used in the fast paced transfer of water and sand slurry at hydraulic fracturing sites.

Use:
Designed to work with Dixon King Crimp Sleeves or Ferrules.

Features:
One-piece design eliminates leak path experienced with two-piece threaded systems
Long lasting and dependable forged hammer nut
Durable and safe with reliable hose retention when crimped as specified

Construction:
Frac fittings: machined iron to ASTM standards; zinc plated
Nut: forged steel meeting AISI standards
Buna-N O-ring (O238BU)
Figures 100 and 200 have a metal-to-metal sealing surface; Figure 206 is similar to Figure 200 with a secondary seal to supplement the metal-to-metal design.

Compatibility & Interchange Data:
Interchangeable with current fittings; phase them into your current operation

Safety notes:
400 PSI working pressure with a minimum 4:1 safety factor (hose burst: hose working pressure) is only achieved with: 3" sizes uses standard crimp stem
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Description	Male fitting
Factory Part Number	HUM206300CS
Includes	Nut, O-ring
Mandatory Pkg/Box Qty	1
Material	Forged steel nut, Iron fitting
Seal	Buna-N
Size	3"
Style	Figure 206
Weight Lb	12.8000
Working Pressure	400 PSI at 70°F (21°C)

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us