DIXON® COMPLETE ASSEMBLY FRAC FITTING

DATE
: 11/23/2026 06:50 PM

SKU
: 15832

BRAND
: DIXON VALVE

MODEL
: HUMF206600CS



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

Applications:
Used in the fast paced transfer of water and sand slurry at hydraulic fracturing sites.

Use:
Designed to work with Dixon King Crimp Ferrules.

Features:
One-piece design eliminates leak path experienced with two-piece threaded systems

Construction:
Frac fittings: machined iron to ASTM standards; zinc plated
Nut: forged steel meeting AISI standards
Buna-N Oring (O440BU)
Figure 200 has a metal-to-metal sealing surface and Figure 206 is similar to Figure 200 with a secondary seal to supplement the metal-to-metal design.

Compatibility & Interchange Data:
Interchangeable with current fittings; phase them into your current operation

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov
230 PSI at 70°F (21°C) 4:1 safety factor

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Description	Male/female complete assembly
Factory Part Number	HUMF206600CS
Mandatory Pkg/Box Qty	1
Material	Iron/Steel
Size	6"
Style	Figure 206
Weight Lb	69.0500
Working Pressure	230 PSI at 70°F (21°C)

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us