SINGLE CLAPPER SIAMESE CONNECTION BACK OUTLET



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 06:05 PM

SKU
: 15907

BRAND
: DIXON VALVE

MODEL
: ISCS4025F

Applications:
Provides the required 500 GPM minimum to supplement the fire protection as an auxiliary inlet connection to the water supply. (250 GPM minimum per inlet.)

Specifications:
UL listed
ULC listed
Factory Mutual approved

Features:
The swing clapper design provides an unobstructed waterway.
Exposed Fire Department Connections (FDC) provide an economical method of satisfying local fire codes.

Construction:
Single swing clapper with (2) pin lug swivel inlets.

Available Options:
Other thread options are available. Consult Dixon for pricing and availability.

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Branding	Auto-Sprinkler
Factory Part Number	ISCS4025F
Inlet	(2) 2-1/2" female NST (NH)
Material	Cast Brass
Maximum Operating Pressure	250 PSI
Origin	Global
Outlet	4" female NPT
Weight Lb	7.5000

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us