GROOVED LIGHTWEIGHT FLEXIBLE COUPLING- SERIES L, STYLE 10



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 09:30 PM

SKU
: 24857

BRAND
: DIXON VALVE

MODEL
: L010

Applications:
Applications include: general purpose, mining, irrigation, and compressed air where a deflection of 5% or less is required.

Use:
Designed for applications requiring moderate internal pressure or where weight is a factor.

Specifications:
Underwriters Listed
Factory Mutual approved
Bolts: 2
Bolt Size: 3/4"
Bolt Length: 4-1/4"

Features:
Comparable to Victaulic's #75 and Grinnell's #7000

Construction:
Rust inhibiting paint

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Factory Part Number	L010
Material	Ductile Iron
Maximum Operating Pressure	350 PSI at 70°F (21°C)
Nominal Size	10"
Pipe OD	10.750"
Seal	EPDM
Weight Lb	12.5000

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us