VENT-LOCK? SAFETY CAM & GROOVE TYPE C COUPLER X HOSE SHANK





** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 11:55 PM

SKU
: 16208

BRAND
: DIXON VALVE

MODEL
: L150-C-SS

Applications:
Transfer of fluids and solids, with a safe disconnection

Use:
Can be used with ferrules, sleeves, bands and other reliable attachment options

Features:
Safety release cam and groove couplings permit the release of static pressure when disconnecting hose assemblies
Venting system protects operator from being sprayed with hazardous or non-hazardous fluids or solids
Safety orange cam arms
US Pat. 934759, CDN Pat. 277866

Available Options:
Consult Dixon for availability of other materials

Safety notes:
Pressure rating recommendation is based on the use of mating Vent-Lock™ L-style fittings at ambient temperature 70°F (21°C) with standard Buna-N seal installed, for use at elevated temperature or other unusual operating conditions, consult Dixon.
Does not interchange with standard cam and groove products use only with Vent-Lock™ L-style fittings.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Material	316 Stainless Steel
Maximum Operating Pressure	250 PSI
Factory Part Number	L150-C-SS
Seal	Buna-N
Size	1-1/2"
Weight Lb	1.6490

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us

www.kmxusa.us