SERIES 1 JUMBO MICRO-FOG LUBRICATOR WITH HIGH PRESSURE SIGHT FEED DOME



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/24/2026 01:03 AM

SKU
: 24873

BRAND
: DIXON VALVE

MODEL
: L17-800APX

Applications:
Designed for use with alcohol or other anti-freeze agents when units are installed in cold temperature environments.
Micro-fog lubricators are used for applications containing one or more points of lubrication, cylinders and multiple or single tools.

Features:
Metal Bowl with Sight Glass
1 qt. reservoir
Oil level sight gauge
High pressure dome with aluminum case and fluorocarbon O-Rings and seals;
High pressure sight glass on bowls and metal petcock drain.
Particle removal per ISO 8573-1, class 5 and class 3
One turn threaded bowl attachment permits easy maintenance

How it works:
Air flow through the lubricator lifts oil from the reservoir to the sight-feed dome. Oil is dropped into the fog generator and atomized into a fine mist. Lightweight particles are delivered downstream for lubrication. Heavier particles fall back into the reservoir.
The micro-fog lubricator delivers 10% of the oil drops visible through the transparent sight-feed dome.

Safety notes:
FRL's are designed for air service only, unless otherwise indicated.
Micro-fog lubricators cannot be filled under pressure.
SCFM ratings at 90 PSIG inlet pressure
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Factory Part Number	L17-800APX
Flow	275 SCFM
Maximum Temperature	175°F (79°C)
Port	1"
Weight Lb	3.0000

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us