WILKERSON FRL'S L30 ECONOMIST® STANDARD LUBRICATOR



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/24/2026 01:21 AM

SKU
: 26418

BRAND
: DIXON VALVE

MODEL
: L30-08AMB

Use:
The rate of oil delivery may be controlled by turning the adjusting screw counter clockwise for more and clockwise for less oil delivery. The oil delivery rate will change automatically to deliver more oil during higher air flows and less oil for air flows lower than the one at which the setting was made.
Can be filled under pressure
For all Wilkerson lubricators, use any petroleum-base, non-detergent light weight oil (SAE 10/150 SSU) which will readily break up into a mist, i.e., Mobil DTE light or comparable oil. Do not use any synthetic oil or oils containing additives or solvents.

Features:
26 oz. bowl
Metal Bowl
Manual brass petcock drain

Safety notes:
FRL\'s are designed for air service only, unless otherwise indicated.
SCFM ratings at 120 PSIG inlet pressure
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Description	Metal Bowl, manual brass petcock drain
Factory Part Number	L30-08AMB
Flow	374 SCFM
Maximum Operating Pressure	200 PSIG (13.8 Bar)
Port	1"
Temperature Range	32°F to 150°F (0°C to 65.5°C)
Weight Lb	5.7600

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us