VENT-LOCK? SAFETY CAM & GROOVE TYPE A ADAPTER



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 10:46 PM

SKU
: 16233

BRAND
: DIXON VALVE

MODEL
: L400-A-AL

Applications:
Transfer of fluids and solids, with a safer disconnection

Use:
Can be used with ferrules, sleeves, bands and other reliable attachment options

Features:
Safety release cam and groove couplings permit the release of static pressure when disconnecting hose assemblies
Venting system protects operator from being sprayed with hazardous or non-hazardous fluids or solids
US Pat. 934759, CDN Pat. 277866

Available Options:
Consult Dixon for availability of other materials

Safety notes:
Pressure rating recommendation is based on the use of mating Vent-Lock™ L-style fittings at ambient temperature 70°F (21°C) with standard Buna-N seal installed, for use at elevated temperature or other unusual operating conditions, consult Dixon.
Does not interchange with standard cam and groove products use only with Vent-Lock™ L-style fittings.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Material	Aluminum
Factory Part Number	L400-A-AL
Size	4"
Weight Lb	1.8500
Working Pressure	150 PSI with King Crimp ferrules, crimp sleeves and bands at 100 PSI

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us

www.kmxusa.us