SERIES 1 FRL'S COMPACT MICRO-FOG LUBRICATOR WITH HIGH PRESSURE SIGHT FEED DOME



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 11:54 PM

SKU
: 26441

BRAND
: DIXON VALVE

MODEL
: L73M-4MBPX

Applications:
Designed for use with alcohol or other anti-freeze agents when units are installed in cold temperature environments.
Micro-fog lubricators are used for applications containing one or more points of lubrication, cylinders and multiple or single tools.

Use:
Recommended lubricants: misting type oil rated 50 to 200 SSU (ISO Grade 7 to 46) at 100°F (38°C)

Features:
Metal Bowl with Sight Glass
4 oz. reservoir
Quick release bayonet bowl
Micro-fog design delivers aerosol mist

Construction:
High pressure sight feed dome with aluminum case and fluorocarbon O-rings and seals
High pressure sight glass on bowls and metal petcock drain

How it works:
Air flow through the lubricator lifts oil from the reservoir to the sight-feed dome. Oil is dropped into the fog generator and atomized into a fine mist. Lightweight particles are delivered downstream for lubrication. Heavier particles fall back into the reservoir.
The micro-fog lubricator delivers 10% of the oil drops visible through the transparent sight-feed dome.

Installation
In-line or modular installation

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

Safety notes:

FRL\'s are designed for air service only, unless otherwise indicated.

Micro-fog lubricators cannot be filled under pressure.

Pressure rating given at ambient temperature 70°F/21°C.

SCFM ratings at 90 PSIG inlet pressure

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	L73M-4MBPX
Flow	60 SCFM
Maximum Temperature	175°F (79°C)
Port	1/2"
Weight Lb	0.9150

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us