L74 SERIES 1 FRL'S STANDARD OIL-FOG LUBRICATOR



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/24/2026 01:37 AM

SKU
: 26443

BRAND
: DIXON VALVE

MODEL
: L74C-3MB

Applications:
Oil-fog lubricators, identified by a green adjusting screw, are used for lubricating a single air tool or air motor, and are located as near the device as possible.

Use:
Recommended lubricants: misting type oil rated 50 to 200 SSU (ISO Grade 7 to 46) at 100°F

Features:
Metal Bowl
7 oz. reservoir
Quick release bayonet bowl
Can be filled under pressure

How it works:
All the oil visible dropping through the transparent sight-feed dome goes to the airstream.

Installation
In-line or modular installation

Safety notes:
FRL\'s are designed for air service only, unless otherwise indicated.
Pressure rating given at ambient temperature 70°F.
SCFM ratings at 90 PSIG inlet pressure
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Description	Metal Bowl
Factory Part Number	L74C-3MB
Flow	118 SCFM
Maximum Operating Pressure	250 PSI
Maximum Temperature	175°F (79°C)
Port	3/8"
Weight Lb	1.8200

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us