WILKERSON FRL'S M18 COMPACT MODULAR COALESCING FILTER



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 07:41 PM

SKU
: 26462

BRAND
: DIXON VALVE

MODEL
: M18-03A

Applications:
High-efficiency removal of water, oil aerosols, and solid particulate contaminants down to 0.01 mg/m³ with minimum pressure drop

Use:
A standard airline filter should be installed as a pre-filter when using a coalescing filter.

Features:
Modern design and appearance
Light weight
High flow capacity
4 oz. bowl
The differential pressure indicator changes from green to red with pressure loss

Construction:
Transparent bowl and guard

Available Options:
0.5 micron type B and 0.003 micron type D elements are optional

Installation
Can be installed in modular system

Safety notes:
FRL\'s are designed for air service only, unless otherwise indicated.
A standard airline filter should be installed as a pre-filter when using a coalescing filter.
SCFM ratings at 150 PSIG inlet pressure
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Description	Automatic Drain
Factory Part Number	M18-03A
Flow	36 SCFM
Maximum Operating Pressure	150 PSIG (10.3 Bar)
Size	3/8"
Temperature Range	32°F to 125°F (0°C to 52°C)
Weight Lb	1.1000

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us