MULTIPORT NEEDLE VALVE

DATE
: 11/23/2026 06:15 PM

SKU
: 16586

BRAND
: DIXON VALVE

MODEL
: MFS20604



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

Specifications:
Flow coefficient: 0.44
Metal-to-metal hard seat design is 100% helium leak tested to 1 x 10-4 ml/s at 200 PSI

Features:
Reduces the number of gauge and other instrument connections to permanent piping installations, decreasing possible leak paths
FKM O-ring and PTFE back- up ring below the threads protects from corrosion and galling
Stem threads are rolled for strength and ease of operation

Construction:
Male to Female
316 Stainless Steel Stem
Handle Style: T Design

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Orifice	0.187"
Thread	NPT
Thread Size	3/4" - 14
Factory Part Number	MFS20604
Material	316 Stainless Steel
Port	1/2" female NPT

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Pressure Rating	10000 PSI at 200°F (10000 PSI at 94°C)
Seal	FKM O-ring
Seat	Hard Seat
Weight Lb	1.3400

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us