BLEED NEEDLE VALVE

DATE
: 11/23/2026 05:52 PM

SKU
: 16754

BRAND
: DIXON VALVE

MODEL
: MS802



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

Specifications:
Metal-to-metal hard seat design is 100% helium leak tested to 1 x 10-4 ml/s at 200 PSI

Features:
Provides a convenient means to relieve process pressures trapped between a shut-off valve and the instrument.
FKM O-ring and PTFE back- up ring below the threads protects from corrosion and galling
Stem threads are rolled for strength and ease of operation

Construction:
316 Stainless Steel Stem
Handle Style: T Design
0.159" bleed port

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Male Thread	NPT
Male Thread Size	1/4" - 18
Style	Hard Seat
Factory Part Number	MS802
Material	316 Stainless Steel
Pressure Rating	10000 PSI at 200°F (10000 PSI at 94°C)

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Seal	FKM O-ring
Weight Lb	1.3700

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us