# BLEED NEEDLE VALVE

DATE
: 11/23/2026 09:37 PM

SKU
: 16756

BRAND
: DIXON VALVE

MODEL
: MS852




** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

Specifications:
Metal-to-metal hard seat design is 100% helium leak tested to 1 x 10-4 ml/s at 200 PSI

Features:
Provides a convenient means to relieve process pressures trapped between a shut-off valve and the instrument.
FKM O-ring and PTFE back- up ring below the threads protects from corrosion and galling
Stem threads are rolled for strength and ease of operation
Features a non-rotating soft tip stem and a back-up metal-to-metal seal

Construction:
316 Stainless Steel Stem
Handle Style: T Design
0.159" bleed port

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

## TECHNICAL SPECIFICATIONS

| | |
|---|---|
| **Male Thread** | NPT |
| **Male Thread Size** | 1/4" - 18 |
| **Style** | Soft Tip |
| **Factory Part Number** | MS852 |
| **Material** | 316 Stainless Steel |
| **Pressure Rating** | 6000 PSI at 200°F (6000 PSI at 94°C) |



2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

## TECHNICAL SPECIFICATIONS

| | |
|---|---|
| **Seal** | FKM O-ring |
| **Weight Lb** | 1.3400 |



KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us