SPIRAL HOSE AND CABLE PROTECTION STANDARD



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 11:47 PM

SKU
: 17038

BRAND
: DIXON VALVE

MODEL
: NFSGX90

Applications:
Used in mining, quarrying, forestry, offshore industries and most hydraulic hose applications

Use:
Can be used on single or multiple hose bundles

Features:
Not flame retardant
Crush and high abrasion resistance
Chemical and UV ray resistant
Self-lubricating to reduce hose wear
Easy to install on-site
Smooth radius on all edges

Note:
Sold in coil lengths only
Spiral guard ID is equal to the guard at rest

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Factory Part Number	NFSGX90
Nominal ID	2.83"
Range	3.15" to 4.30"
Temperature Range	-40°F to 248°F (-40°C to 120°C)
Weight Lb	54.6000

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us