NK-SERIES JAPANESE PNEUMATIC MALE THREADED PLUG

DATE
: 11/24/2026 12:11 AM

SKU
: 17050

BRAND
: DIXON VALVE

MODEL
: NK2BM2





Construction:
Machined components are manufactured using solid steel bar stock.
Steel componentry is plated using ROHS Compliant Trivalent Chrome.

Compatibility & Interchange Data:
Japanese Industrial Interchange Pneumatic Coupling
Nitto Kohki Hi-cupla 200, Rectus Series 13 and CEJN Series 315

Safety notes:
It is important to be safe when installing quick disconnect couplings into a pneumatic circuit. Never install a pneumatic coupling directly into an air tool, use a piece of hose that is at least 18" long, between the tool and the coupling, to prevent damage to the coupling. To protect the operator, safety devices, such as a safety check valve and safety cable should be installed in case there is a hose or coupling failure.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	1/4"
Burst Pressure	13500 PSI
Factory Part Number	NK2BM2
Hex	5/8"
Length	1.54"
Material	Steel
Maximum OD	0.52"
Maximum Operating Pressure	300 PSI

** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	BSPT
Thread Size	1/4"
Weight Lb	0.0500

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us