DUAL-LOCK P-SERIES THOR INTERCHANGE MALE THREAD PLUG





** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 08:36 PM

SKU
: 17161

BRAND
: DIXON VALVE

MODEL
: P4M4

Construction:
Machined components are manufactured using solid bar stock.
Nitrile (Buna-N) seals are standard

Compatibility & Interchange Data:
Thor Finger-Lock Interchange
Interchanges with National A type, Campbell Double-Lock and Thor PHC series couplings

Safety notes:
It is important to be safe when installing quick disconnect couplings into a pneumatic circuit. Never install a pneumatic coupling directly into an air tool, use a piece of hose that is at least 18" long, between the tool and the coupling, to prevent damage to the coupling. To protect the operator, safety devices, such as a safety check valve and safety cable should be installed in case there is a hose or coupling failure.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	1/2"
Burst Pressure	2600 PSI (180 bar)
Factory Part Number	P4M4
Length	2.25" (57.2mm)
Material	Steel
Maximum OD	1.55" (39.4mm)
Maximum Operating Pressure	300 PSI (20 bar)
Temperature Range	-40°F to +250°F (-40°C to +121°C)

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Thread	NPTF
Thread Size	1/2"
Weight Lb	0.2750
Wrench Flat	15/16"

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us

www.kmxusa.us