PROCESS GAUGE



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 05:07 PM

SKU
: 17237

BRAND
: DIXON VALVE

MODEL
: PGS60

Applications:
Specifically designed for process, chemical and petroleum industries, these process gauges are engineered to deliver years of accurate service while withstanding vibration, corrosive media and corrosive atmosphere.

Specifications:
Accuracy: ± 0.5% ANSI/ASME Grade 2A

Construction:
Case: black impact resistant thermoplastic, with safety blowout back, solid front, integral back flange (dry)
Ring: ethylene propylene
Wetted parts: 316L stainless steel
Window: polycarbonate
Dial: white aluminum
Scale: single scale PSI only
Pointer: black aluminum

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Factory Part Number	PGS60
Figure Interval	10
Minor Gradient	.5
Mount	1/2" Lower Mount
Pressure Range	0-60 PSI
Size	4-1/2" Face
Temperature Range	-40°F to 200°F (-40°C to 93°C)
Weight Lb	2.0300

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us