IN-LINE LUBRICATOR 1"



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 07:08 PM

SKU
: 17247

BRAND
: DIXON VALVE

MODEL
: PL500

Applications:
Designed to protect portable or stationary air tools by efficiently oiling the tool mechanisms.
Each time an air tool is operated, a fine mist of oil is injected into it along with the air from the compressor.

Use:
Type of oil to use: Use any petroleum-based, non-detergent light weight oil (SAE 10/150SSU) which will readily break up into a mist, i.e., Mobil DTE light or comparable oil.

Features:
Transparent sight disc allows visual inspection of oil level.
Oil flow regulated by screwdriver screw adjustment.
Minimum flow rate is 30 SCFM.

Construction:
Aluminum

Installation
Installation is recommended within 25 feet of the tool to be lubricated.
Refer to the arrow for proper air flow direction.

Safety notes:
Not recommended for constant flow applications. For reciprocating tools only.
Do not use any synthetic oil or oils containing additives or solvents.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Capacity	16.0 fluid oz. oil (454.5ml)
Factory Part Number	PL500
Female Thread	NPT
Female Thread Size	1" (25mm)
Flow	100 SCFM
Material	Aluminum
Maximum Operating Pressure	250 PSI at 70°F (21°C)
Weight Lb	4.6800

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us