TRUESEAL? BALL VALVE FEMALE CONNECTOR



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/24/2026 01:01 AM

SKU
: 17316

BRAND
: DIXON VALVE

MODEL
: PP4VFC2-MG

Applications:
These corrosion resistant, all-plastic designed ball valves are ideal for water filtration units, coffee and beverage machines and a wide variety of other fluid applications.

Specifications:
FDA compliant
NSF-51 listed for contact with food
Certified to NSF-61

Features:
EPDM seal secures connection with larger surface area than standard O-rings
Full flow self-cleaning ball
High-temperature, scale resistant Polysulfone ball

Construction:
Glass-reinforced Polypropylene body
O-ring seal material: EPDM

Safety notes:
Actual working pressures will be lower at elevated temperatures.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Burst Pressure	600 PSI
Factory Part Number	PP4VFC2-MG
Female Thread	NPTF
Female Thread Size	1/8"
Material	Polypropylene
Maximum Operating Pressure	150 PSI
Seal	EPDM
Temperature Range	0°F to 225°F (-18°C to 107°C)
Tube OD	1/4"
Weight Lb	0.0440

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us