POLYPROPYLENE CAM & GROOVE TYPE A ADAPTER X FEMALE NPT



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 09:45 PM

SKU
: 17346

BRAND
: DIXON VALVE

MODEL
: PPA200

Applications:
Designed for use with liquids, consult Dixon for specific recommendations

Construction:
Manufactured from glass-filled polypropylene

How it works:
To make a connection, simply slide the adapter into the coupler and with normal hand pressure, press the cam levers down.
Uncoupling is as quick and simple as coupling. Just lift the cam arms and remove the adapter.

Safety notes:
Under no circumstances should cam and groove couplings be used for compressed air or steam service!
Pressure rating is based on the seal of the mating part
Pressure rating recommendations are based on the use of mating Dixon® fittings at ambient temperature 70°F (21°C) with a standard seal installed. For use at elevated temperature or other unusual operating conditions, consult Dixon®.
NOT recommended for use with PTFE gaskets
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Material	Polypropylene
Maximum Operating Pressure	100 PSI
Factory Part Number	PPA200
Size	2"
Weight Lb	0.2800

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us

www.kmxusa.us